

Progress on developing the spherical tokamak for fusion applications

Jonathan Menard¹

T. Brown¹, J. Canik², J. Chrzanowski¹, L. Dudek¹, L. El Guebaly³, S. Gerhardt¹, S. Kaye¹,
C. Kessel¹, E. Kolemen¹, M. Kotschenreuther⁴, R. Maingi², C. Neumeyer¹,
M. Ono¹, R. Raman⁵, S. Sabbagh⁶, V. Soukhanovskii⁷, T. Stevenson¹,
R. Strykowski¹, P. Titus¹, P. Valanju⁴, G. Voss⁸, A. Zolfaghari¹,
and the NSTX Upgrade Team

¹Princeton Plasma Physics Laboratory, Princeton, NJ 08543

²Oak Ridge National Laboratory, Oak Ridge, TN, USA

³University of Wisconsin, Madison, WI, USA

⁴University of Texas, Austin, TX, USA

⁵University of Washington, Seattle, WA, USA

⁶Columbia University, New York, NY, USA

⁷Lawrence Livermore National Laboratory, Livermore, CA, USA

⁸Culham Centre for Fusion Energy, Abingdon, Oxfordshire, UK

24th IAEA Fusion Energy Conference
San Diego, USA
8-13 October 2012

Outline (page 1)

1. Title page
 2. Outline
 3. Overview: Role/mission of ST in fusion (FNSF, ITER, Pilot)
 4. Motivation for NSTX-U and recent FNSF studies
 - Recent NSTX progress/achievements toward FNSF (microtearing, stability/disruptions)
 - Gaps to FNSF
 - Motivation for NSTX Upgrade to narrow/fill gaps
 - FNSF studies since Pilot Plant studies
-
5. CHI and non-inductive ramp-up calculations using TSC (Raman+Kessel)
 - Mention benefits of ECH (5 year plan)
 6. Non-inductive sustainment calculations vs. range of parameters
 - Few key projections/results from Menard/Gerhardt papers
 7. Divertor studies:
 - Snowflake performance, feasibility in NSTX-U, possibility of cryo-pumping (5 yr plan)

Outline (page 2)

9. Pictures of test-cell clearance, progress on interior/exterior of vessel
 10. Centerstack status/progress
 - Fault → new soldering method, friction-stir welding, flex joints, VPI, OH winding plans
 11. 2nd NBI status/progress
 - NBI port, NBI box lift, beam dump
-

9. ST-FNSF parameters vs. R for fixed wall loading
 - Include achievable engineering Q vs. thermal efficiency and size
 10. Device/coil layout for actual equilibrium
 - PF coils at ends of CS – UW calcs, Ali Z to check insulator capabilities
 - Removable top-lid, horizontal modular divertor maintenance
 - Show design of Bitter coils for PF magnets at ends of TF
 11. Divertor heat flux projections
 - without and with snowflake
 - Impact of snowflake on device layout
 12. TBR calculations – 2D and any 3D (in progress)
-

13. Summary