Google: [Leonid Zakharov] → http://w3.pppl.gov/~zakharov

Disruptions, eddy currents, tile damage, Hiro currents, and grounding of LLD

Leonid E. Zakharov

Princeton Plasma Physics Laboratory, MS-27 P.O. Box 451, Princeton NJ 08543-0451

Presented by Leonid E. Zakharov

NSTX Research Forum

PPPL, Princeton NJ, March 16, 2011

¹This work is supported by US DoE contract No. DE-AC02-09-CH11466.



Contents

1	M.Ono: LLD is reinstalled on NSTX	3
2	Tiles, LLD and Hiro currents	4





1 M.Ono: LLD is reinstalled on NSTX

Liquid lithium divertor target system commissioned

Utilized in four LLD experimental proposals in three campaigns



LLD plate covered with lithium Significant over-flow evident consistent with evaporating 2 x fill capacity



- Plasma surface heating raised the LLD surface temperature to ~ 200 250 °C.
- No significant moly surface damage or moly influx observed.
- Damage discovered after operations. Plasma disruptions caused mechanical support and arcing damages. Explains why electrical heaters failed. Air heater has worked well but the heating tubes were arc damaged.
- LLD plates being reinstalled with improvements in the mechanical support structure and grounding. No active heaters but will utilize plasma heating.



M. Ono Research Forum

March 15, 2011





2 Tiles, LLD and Hiro currents

For protection of the PFC against plasma disruptions the conventional wisdom can be summarized as:

- 1. Eddy currents should be broken.
- 2. Plasma Facing Conducting Surfaces (PFCS) should have a tile based design.
- 3. The grounding should be point-wise (in the middle of the tile).
- 4. The same is applicable for LLD sectors (considered as "tiles").

New understanding of disruptions suggests that:

- 1. Eddy currents are a relatively minor effect in disruyptions.
- 2. Instead, the Hiro currents represent the dominant effct.
- 3. Hiro currents cannot be eliminated by tiling PFCS.
- 4. In order to mitigate (eliminate) the effect of arcing it is necessary to facilitate the flow of the Hiro currents by an appropriate grounding.



