

Suggested staging of PFC upgrades  
(Assuming high-Z conversion of divertors and  
cryo-pump are “givens”)


MA Jaworski  
Dec 10, 2012

# Baseline budget

Strawman  
(More)

First major outage

... by 2018 assuming base budget  
and you to better define schedule)



# Staged upgrade logic (years 1&2)

- Expect limited outage between years 1 and 2
- Startup all carbon for years 1 and 2
  - High heat-flux capability on all surfaces to demonstrate full-power NSTX-U, minimum PFC risk
  - Establish material migration diagnostics and upward lithium application (and MAPP)
  - Notional MPTSG Milestone 1: determine role of coverage vs. deposition quantity in determining performance increase in NSTX-U
- Characterize B+C vs. Li+C operation in preparation for change to Li+TZM upgrade

# Staged upgrade logic (year 3)

- Expect major outage in between years 2-3
- Install molybdenum tile divertor in upper divertor (IBDU-H/V)
- Validate new tile design for NSTX-U conditions
- Direct comparison between B+C, Li+C and Li+TZM with data from years 1&2
- **Notional MPTSG Milestone 2: Determine local and global transport of high-Z material (uncoated experiments) and low-Z material in NSTX under standard divertor configurations (MAPP XPS for composition of redeposited material); determine Mo core contamination**
- Begin vapor shielding studies with Li coatings on Mo tiles

# Staged upgrade logic (year 4)

- Major machine outage to install cryo
  - Install in upper divertor
  - Install with high-Z PFCs to fully convert upper PFCs
- Key experimental comparison: high-Z+cryo (USN) vs. C+Li (LSN)
  - Also compare high-Z+Li+cryo in conventional vs. vapor shielded plasmas
- Avoid the potentially nasty surprise of attributing local retention via C+Li to cryo and *then* upgrading surrounding PFCs to high-Z
- Avoid double-sets of PFCs by upgrading straight to high-Z

# Staged upgrade logic (year 5)

- Use data from year 3-4 on high-Z tile design to iterate design for lower divertor
- **Notional MPTSG Milestone 3: Demonstrate high-performance, high-power plasmas with vapor-shielded PFCs**
  - Example case: high-performance, high-power discharges with double-null geometry, vary flux expansion to really “cook” PFCs – push vapor-shielded regime to limits
  - Measure material migration in these plasmas to begin establishing liquid metal inventory control schemes
  - Length of duration to be determined by local transport of material (i.e. redeposition fractions)
- Provides basis for fully-flowing liquid metal module in lower divertor for long-pulse vapor-shielding