


XP LLD-1 Decommissioning

H. W. Kugel, T. Gray, J. Canik,
and the NSTX Research Team

NSTX Research Forum
PPPL
December, 1-3, 2009

College W&M
Colorado Sch Mines
Columbia U
CompX
General Atomics
INEL
Johns Hopkins U
LANL
LLNL
Lodestar
MIT
Nova Photonics
New York U
Old Dominion U
ORNL
PPPL
PSI
Princeton U
Purdue U
SNL
Think Tank, Inc.
UC Davis
UC Irvine
UCLA
UCSD
U Colorado
U Illinois
U Maryland
U Rochester
U Washington
U Wisconsin



Culham Sci Ctr
U St. Andrews
York U
Chubu U
Fukui U
Hiroshima U
Hyogo U
Kyoto U
Kyushu U
Kyushu Tokai U
NIFS
Niigata U
U Tokyo
JAEA
Hebrew U
Ioffe Inst
RRC Kurchatov Inst
TRINITI
KBSI
KAIST
POSTECH
ASIPP
ENEA, Frascati
CEA, Cadarache
IPP, Jülich
IPP, Garching
ASCR, Czech Rep
U Quebec

XP LLD-1 Decommissioning

- **LLD-1 Commissioning and Decommissioning**

- XP LLD-1 Commissioning will start at 205°C. Administrative decision points may allow measurements at higher LLD-1 temperatures (<350°C) depending on the measured thermal response to NBI.
- XP LLD-1 Decommissioning will raise LLD-1 temperature >350-500°C to evaporate all lithium from the LLD-1 pores prior to venting.

- **Purpose**

- As the sum total lithium pressure on the plasma due to lithium evaporation and sputtering exceeds the deuterium plasma pressure (~400°C), characterize lithium core concentration, neutron production, edge shielding, SOL physics, and plasma performance.
- Empty the LLD-1 prior to venting.

- **Method**

- Raise LLD-1 temperature slowly to 400-500°C and operated at this temperature until all lithium is evaporated from LLD-1.
Use reference discharges for R=0.75m

- **Required Run Time**

- 0.5-1 day at end of run as the final XP.

