


# Characterize plasma near planned plenum entrance position

*Coll of Wm & Mary  
 Columbia U  
 CompX  
 General Atomics  
 FIU  
 INL  
 Johns Hopkins U  
 LANL  
 LLNL  
 Lodestar  
 MIT  
 Lehigh U  
 Nova Photonics  
 ORNL  
 PPPL  
 Princeton U  
 Purdue U  
 SNL  
 Think Tank, Inc.  
 UC Davis  
 UC Irvine  
 UCLA  
 UCSD  
 U Colorado  
 U Illinois  
 U Maryland  
 U Rochester  
 U Tennessee  
 U Tulsa  
 U Washington  
 U Wisconsin  
 X Science LLC*

**J.M. Canik, ORNL**



**NSTX-U Research Forum  
 Princeton, NJ  
 2/26/15**



*Culham Sci Ctr  
 York U  
 Chubu U  
 Fukui U  
 Hiroshima U  
 Hyogo U  
 Kyoto U  
 Kyushu U  
 Kyushu Tokai U  
 NIFS  
 Niigata U  
 U Tokyo  
 JAEA  
 Inst for Nucl Res, Kiev  
 Ioffe Inst  
 TRINITI  
 Chonbuk Natl U  
 NFRI  
 KAIST  
 POSTECH  
 Seoul Natl U  
 ASIPP  
 CIEMAT  
 FOM Inst DIFFER  
 ENEA, Frascati  
 CEA, Cadarache  
 IPP, Jülich  
 IPP, Garching  
 ASCR, Czech Rep*

# Cryo pump performance is sensitive to plasma parameters near pump entrance

- Physics design of NSTX-U cryo is based on the DIII-D design of pumping in the SOL
- Achievable plenum pressure is strongly dependent on the plasma parameters near the plenum entrance
  - Predicted by analytic modeling
  - Confirmed by DIII-D experiments
  - Results in sensitivity to OSP position
- To make meaningful predictions, we need to know  $n_e$ ,  $T_e$ , particle flux near where the entrance is likely to be
  - Strong assumptions used to project in NSTX-U
    - Ip scaling of SOL width for heat flux
    - Assume  $T_e \sim 15$  eV
  - Sanity check needed using NSTX-U measurements to confirm physics design



Maingi, NF 99

# Proposal: run with OSP near planned pump entrance during B phase

- Conventional ELMy + cryo scenario is backup should particle control with lithium prove too challenging
  - Important to get data during B phase of NSTX-U ops
- Cross-TSG  $I_p/B_t/P_{\text{NBI}}$  scans should provide most of the data needed to confirm cryo projections
  - Provided IRTV, probes are working/running
  - Probably restricted to shapes with OSP on inner divertor
- Proposal aims for data that is unlikely to be gathered via piggybacking during early operations
  - Primary target is impact of strike point position on pumping (plasma parameters near planned cryo entrance (at  $R \sim 0.72$ ))
  - Run downward biased shape with OSP on bullnose tile
  - Scan OSP outwards to  $R \sim 0.75$  (high-Z shape?)
  - Other scans ( $I_p, P, f_{\text{exp}}$ ) would be nice but lower priority