


High Harmonic Fast Wave Progress and Plans

Gary Taylor

Mario Podestà, Nikolai Gorelenkov

**NSTX PAC-29
PPPL B318
January 26-28, 2011**

College W&M
Colorado Sch Mines
Columbia U
CompX
General Atomics
INL
Johns Hopkins U
LANL
LLNL
Lodestar
MIT
Nova Photonics
New York U
Old Dominion U
ORNL
PPPL
PSI
Princeton U
Purdue U
SNL
Think Tank, Inc.
UC Davis
UC Irvine
UCLA
UCSD
U Colorado
U Illinois
U Maryland
U Rochester
U Washington
U Wisconsin




Culham Sci Ctr
U St. Andrews
York U
Chubu U
Fukui U
Hiroshima U
Hyogo U
Kyoto U
Kyushu U
Kyushu Tokai U
NIFS
Niigata U
U Tokyo
JAEA
Hebrew U
Ioffe Inst
RRC Kurchatov Inst
TRINITI
KBSI
KAIST
POSTECH
ASIPP
ENEA, Frascati
CEA, Cadarache
IPP, Jülich
IPP, Garching
ASCR, Czech Rep
U Quebec

Outline

- Role of HHFW in NSTX Program
- Status of HHFW Research & Response to PAC-27
- HHFW Research Plan for FY11-12
- Plans for FY13-14 Outage

HHFW heating & current drive (CD) being developed for non-inductive ramp-up, bulk heating & q(0) control




HHFW Goals

- (1) HHFW couples to start-up plasma
- (2) HHFW for I_p overdrive through bootstrap & HHFW CD
- (3) HHFW generates sufficient I_p to confine NBI ions
- (4) HHFW provides bulk heating & $q(0)$ control in H-mode

- Near-term approach is to heat low- I_p ohmic plasmas and access 100% non-inductive current drive

HHFW double end-fed upgrade was installed in 2009, shifted ground from end to strap center to increase maximum P_{RF}






- Designed to bring system voltage limit with plasma (~ 15 kV) to limit in vacuum (~ 25 kV):
 - Increasing $P_{RF} \sim 2.8$ times
- Antenna upgrade was beneficial:
 - Reached arc-free $P_{RF} \sim 4$ MW after a few weeks of operation at the end of 2009 campaign
- In 2008-9, Li wall conditioning was observed to enhance HHFW coupling by decreasing edge density

PAC27-27

Increased lithium usage in 2010 significantly degraded performance of the upgraded antenna compared to 2009

- In 2010 RF plasma operations started after extensive Li injection, only reached arc-free $P_{RF} \sim 1.4$ MW; observed copious Li ejections during arcs
 - Before run quickly reached stand-off voltage ~ 25 kV during vacuum conditioning
 - After extensive Li injection difficult to reach ~ 15 kV in vacuum
 - Dust seen during plasmas & inside antenna






- For FY11-12 will return to FY09 Li levels:
 - should be okay for HHFW operations
- Tested prototype ELM/arc discrimination system in 2010:
 - Worked well on bench using recorded data, but tripped undesirably 20-30 times during real shot

PAC27-27

PAC27-28

Progress made in sustaining HHFW heating during $I_p=300$ kA RF-only H-mode plasma; $T_e(0) = 3$ keV with only 1.4 MW

- Low I_p HHFW experiments in 2005 could not maintain P_{RF} during H-mode
- Produced sustained RF-only H-mode in 2010:
 - Better plasma-antenna gap control than in 2005, due to reduced PCS latency
 - Modeling predicts $I_{RFCD} \sim 85$ kA, $I_{Bootstrap} \sim 100$ kA $\rightarrow f_{NI} \sim 60\%$
 - High f_{NI} enabled by positive feedback between ITB, high $T_e(0)$ and RF CD
 - $f_{NI} \sim 100\%$ requires $P_{RF} \sim 3$ MW, well below arc-free P_{RF} available in 2009
 - No q-profiles for these RF-only plasmas – MSE-LIF will enable this in FY11-12



PAC27-27
PAC27-29

Adding NBI to $P_{RF} = 1.4 \text{ MW}$, $I_p = 300 \text{ kA}$ plasma resulted in lower f_{NI} due to RF absorption on fast-ions & higher n_e


- Density increased during HHFW heating probably due to fast-ion interaction with the antenna
- Much lower $T_e(0)$ & higher $n_e(0)$ than RF-only H-mode, resulted in $I_{RFCD} \sim 20 \text{ kA}$
- 60% of P_{RF} to electrons, 40% to fast-ions
- $\sim 50\%$ of injected NBI fast-ions are promptly lost at this low current:

➤ Predict $\sim 80\%$ will be confined using more tangential 2nd NBI in NSTX-U

- $I_{\text{Bootstrap}} = 60\text{-}90 \text{ kA}$, $I_{\text{NBICD}} = 50\text{-}70 \text{ kA}$
- $f_{NI} \sim 50\%$


PAC27-27

PAC27-29




Self-consistent finite-orbit-width (FOW) ORBIT-RF/AORSA in good agreement with FIDA data for NBI+HHFW plasmas

Fast-Ion Modeling Status at PAC-27



- HHFW interaction with NBI fast-ion can be significant
- At PAC-27 there was significant disagreement between modeling & FIDA fast-ion profiles
- Good agreement between modeling & FIDA has now been achieved by including additional iterations between AORSA & FOW ORBIT-RF
- Work has also begun on a full FOW correction to CQL3D which is expected to be completed in late 2011

Present Fast-Ion Modeling Status




$P_{\text{NBI}} = 1 \text{ MW}$
 $P_{\text{RF}} = 1 \text{ MW}$

M. Choi, GA


PAC27-28

3-D AORSA full-wave model with 2-D wall boundary predicts large E_{RF} following magnetic field near top & bottom of NSTX



D. L. Green, ORNL

Edge RF eigenmode looks similar to striated structures imaged by visible plasma TV



- In addition to RF power coupling to core, AORSA predicts some RF power propagates just inside LCFS as an edge localized RF eigenmode
- Beginning to make divertor tile current measurements to compare to theory

PAC27-28

HHFW coupling & heating efficiency on NSTX-U

- B_T , I_p and P_{nbi} in NSTX-U will be 2x higher than NSTX, what are the implications for HHFW coupling & heating efficiency on NSTX-U?:
 - Higher B_T in NSTX-U moves fast-wave cut off towards or inside the separatrix, reducing surface wave losses
 - Higher n_e in NSTX-U may increase scrape off density, moving cut off outside separatrix and closer to wall, increasing surface wave losses – although SOL width may shrink at higher I_p
 - Higher P_{nbi} in NSTX-U may cause more fast-ion interactions with antenna, requiring larger antenna-plasma gap
 - Larmor radius (and banana width at high I_p) will be smaller, helping to reduce antenna interaction
- Will revisit higher I_p RF+NBI H-mode plasmas in FY11-12, including discharges with P_{nbi} up to 6 MW
- AORSA modeling of NSTX-U scenarios is also planned for FY11-12

PAC27-28

HHFW research plan for FY11-12 – (1)

- Assess "clean" antenna performance in plasma early in FY11-12 campaign
- Operate antenna strap on test stand to increase standoff voltage in vacuum

1st Priority:

- HHFW coupling at low I_p & during I_p ramp-up (with SFSU TSG):
IOS-5.2 R(12-2)
 - HHFW heating of low I_p plasma
 - Couple HHFW into CHI-initiated plasma
 - Assess I_p ramp-up of an inductively generated discharge to 250-400kA with HHFW + bootstrap current overdrive

2nd Priority:

- Prepare for NSTX-U by running RF+NBI high I_p H-modes at P_{nbi} up to 6 MW: **IOS-5.2, TC-9, TC-14**
 - Study interaction of fast-ions with antenna and antenna heating
 - Study surface waves at maximum available P_{rf} & P_{nbi}
 - Study dependence of heating and CD efficiency on $k_{||}$, outer gap, n_{edge}

ITPA task NSTX milestone

HHFW research plan for FY11-12 – (2)

3rd Priority:

- Many HHFW experiments not started in FY10 due to RF power limitations, if time permits complete these experiments: **IOS-5.2, TC-9, TC-14**
 - HHFW interactions with ELMs & SOL
 - Fast-ion interactions, rotation effects & RFCD

High Priority Modeling Activities:

- Complete full FOW CQL3D
- Benchmark core HHFW CD in RF+NBI H-mode against advanced RF codes upgraded to include interactions with fast-ions
- Use non-linear gyrokinetics modeling to identify source of transport during HHFW heating and compare to that during NBI heating:
 - Especially effect of varying collisionality (microtearing vs ETG)

New & Upgraded Diagnostics will Aid HHFW Research in FY11-12:

- MSE-LiF will provide $q(r)$ without NBI heating
- Additional MPTS channels will improve RF modeling
- Tangential FIDA will improve the study of RF fast-ion interaction

ITPA task NSTX milestone

HHFW plan FY13-14 outage period


- Analysis and publication of low- I_p results, fast-ion interactions, and divertor heating by RF
- RF modeling NSTX-U plasma scenarios with the extended boundary AORSA-3D and full FOW CQL3D codes
- Implement design changes to antenna to minimize Li deposition inside the antenna box:
 - May install double "closed" shield configuration
- Assess possible change to six-strap antenna configuration:
 - Full control of spectral peak location ($\sim 3 - 14 \text{ m}^{-1}$) through arbitrary phasing
 - Simplified, less crowded power distribution system
 - Frees up mid plane port space for possible CAE and/or EHO antenna
 - Would need to increase strap current and maximum system voltage by 40% to obtain same power
 - Run AORSA with six straps to see if there are any unexpected changes

Summary



- Sustained $I_p = 300$ kA RF-only H-mode with $P_{rf} = 1.4$ MW achieved $f_{NI} \sim 60\%$; project $f_{NI} \sim 100\%$ achievable with $P_{RF} \sim 3$ MW
- In FY10 Li compounds inside antenna limited arc-free $P_{RF} \leq 1.4$ MW
- Improved agreement between modeling & FIDA for NBI+HHFW plasmas
- Modeling predicts edge RF eigenmodes may drive significant power flows
- FY11-12 experiments will focus on CHI-initiated, HHFW-heated plasmas and NBI+HHFW H-modes with P_{nbi} up to 6 MW

Backup Slides

NSTX HHFW antenna has well defined spectrum, ideal for studying phase dependence of heating




HHFW antenna extends toroidally 90°



- Phase between adjacent straps easily adjusted between $\Delta\phi = 0^\circ$ to $\Delta\phi = 180^\circ$

Double-fed HHFW antenna operation improved with time in 2009, but degraded over time in 2010




- Operation spread out evenly over ~ 5 months
- Initial plasma conditioning, then majority of time on experiments
- Most operation in 2-3 MW range throughout campaign

- 2009 operation concentrated in last 4 weeks
- Majority of time spent on plasma conditioning
- Operation in 2.5-4 MW range, improved with time

- 2010 operation widely separated over ~4 months
- Almost all time spent on plasma conditioning
- Operation < 3 MW, deteriorated with time

TRANSP-TORIC simulation with no RF coupling losses predicts ~180 kA Bootstrap CD + ~120 kA RFCD



- RF coupling efficiency is typically ~ 60% for H-mode, giving $f_{NI} \sim 60\%$
- TRANSP-TORIC RF CD efficiency of ~ 85 kA/MW
- GENRAY-ADJ RF CD efficiency ~ 115 kA/MW

TRANSP-TORIC analysis of matched NBI+HHFW & NBI-only ELM-free H-modes predicts ~ 50% of P_{RF} is absorbed inside LCFS

- Fraction of P_{RF} absorbed within LCFS (f_A) obtained from TRANSP-calculated electron stored energy:

W_{eX} – from HHFW+NBI H-mode

W_{eR} – from matched NBI-only H-mode

W_{eP} – using χ_e from NBI-only H-mode to predict T_e in HHFW+NBI H-mode


- $f_A = (W_{eX} - W_{eR}) / (W_{eP} - W_{eR}) = 0.53 \pm 0.07$

- TORIC used to calculate the power absorbed by electrons (P_{eP}) assuming 100% RF plasma absorption

- Electron absorption, $P_{eA} = f_A \times P_{eP}$

For $P_{RF} = 1.9$ MW:

- 0.7 MW → electrons
- 0.3 MW → ions



CQL3D Fokker-Planck code predicts significant fast-ion losses in HHFW-heated ELM-free NBI H-modes


- Without fast-ion loss CQL3D predicts much higher neutron production rate (S_n) than is measured

- Simple-banana-loss model predicts S_n just below measured S_n :



- Assumes prompt loss of fast-ions with a gyro radius + banana width > distance to LCFS
- ~ 60% RF power to fast-ions is lost

- For this shot FIDA fast-ion diagnostic measures no change in fast-ion density during HHFW heating

- First-order finite-orbit width loss model being implemented in CQL3D




Slow fall of P_{RF} results in sustainment of high $T_e(0)$ and core electron heating even down to $P_{RF} < 1.4$ MW




- Slow transition to H-mode from L-mode as power is ramped to 3.7MW
- During slow ramp down of P_{RF} , the core temperature is maintained and broadened in radius even down to 1.36 MW
- Large ELM at even lower power strongly reduces the stored electron energy and marks the transition back to the L-mode


Divertor tile currents are used to track presence of RF fields (sheath) and driven currents



- Tiles in row 3 and 4 of divertor plate are instrumented with Rogowski sensors
- Bay I and K tiles are in line with “hot” zone for RF edge deposition




Divertor tile currents in row 3 show movement of RF hot zone across tiles as magnetic field pitch is increased




- $\Delta I_{\text{tile } 3k}$ decreases and $\Delta I_{\text{tile } 3i}$ increases as magnetic field pitch increases and RF spiral hot zone moves toward the center stack

Tile currents in row 3 are consistent with RF hot zone movement measured with the fast IR camera at Bay H

Fast IR at Bay H vs field pitch
for $t = 0.450$ sec



Shift of RF hot zone
with pitch



- Movement of RF hot zone with magnetic field pitch is relatively fast in the lower pitch range but slows considerably in the higher pitch range