#### Parallel Electron Force Balance and the L-H Transition

# Tim Stoltzfus-Dueck Princeton University

In a popular description of the L-H transition, energy transfer to the mean flows directly depletes turbulence fluctuation energy, resulting in suppression of the turbulence and a corresponding transport bifurcation. However, electron parallel force balance couples nonzonal velocity fluctuations with electron pressure fluctuations on rapid timescales, comparable with the electron transit time. For this reason, energy in the nonzonal velocity stays in a fairly fixed ratio to electron thermal free energy, at least for frequency scales much slower than electron transit. In order for direct depletion of the energy in turbulent fluctuations to cause the L-H transition, energy transfer via Reynolds stress must therefore drain enough energy to significantly reduce the sum of the free energy in nonzonal velocities and electron pressure fluctuations. At low  $k_{\perp}$ , the electron thermal free energy is much larger than the energy in nonzonal velocities, posing a stark challenge for this model of the L-H transition.



ISTX-U November 2, 2016



#### Overview

- Background: paradigms for the L-H transition
- Parallel electron physics and adiabatic response
- Free energy balance
  - for rapid L-H transition
  - ▶ for slow L-H transition
- Conclusions

This work is part of a collaboration with Ahmed Diallo, Stewart Zweben, and Santanu Banerjee, doing experimental investigation of the L-H transition on NSTX with gas puff imaging (GPI). For the experimental work, see e.g.

A. Diallo, Energy Exchange Dynamics across L-H Transitions in NSTX, IAEA FEC 2016  $\rm EX/5$ -3.

A. Diallo, S. Banerjee, S. Zweben, and T. Stoltzfus-Dueck, Energy Exchange Dynamics across L-H transitions in NSTX. GO6 10.

#### Background: Paradigms for the L-H transition

What is the L-H transition?

- sudden transition to a state of good energy confinement in the edge
- appears as heating power increases past some threshold

Most models of L-H transition focus on  $E \times B$  shear and have two parts:

- ightharpoonup Something drives sheared zonal  $\boldsymbol{E} \times \boldsymbol{B}$  flows
  - Nonlinear energy transfer from turbulence to flows via Reynolds stress.
  - ▶ 'Diamagnetic' flow shear due to  $\nabla p_i$  contribution to  $E_r$ .
- Suppression of turbulence by flow shear (two possibilities):
  - 1. Energy transfer to flows directly depletes turbulent fluctuations.
  - 2. Shearing of eddies destroys turbulence in other ways, e.g.
    - Reduce effective growth rate
    - Increase damping

Some experimental investigations consider the following energy balance:

$$\left(E_{\sim} \doteq \int \mathrm{d}\mathcal{V} \, rac{1}{2} n_0 m_i \tilde{v}_E^2 \right)$$

$$n_0 m_i \int d\mathcal{V}(\tilde{v}_E^{\times} \tilde{v}_E^{y}) \partial_x \langle v_E \rangle$$

$$n_0 m_i \int \mathrm{d} \mathcal{V}(\tilde{v}_E^{\times} \tilde{v}_E^{y}) \partial_x \langle v_E \rangle \quad \boxed{E_z \doteq \int \mathrm{d} \mathcal{V} \, \frac{1}{2} n_0 m_i \langle v_E \rangle^2}$$

Hasegawa-Wakatani plus curvature is enough for this problem.

fluctuating part 
$$F \times B$$
 adv  $F \times B$  adv

Assumptions:


$$\mathcal{K} \doteq -\frac{2}{B^2}\hat{\boldsymbol{b}} imes 
abla B \cdot 
abla$$

- isothermal electrons
- single species of cold singly-ionized ions
- purely resistive parallel dynamics
- ▶ shearless, simple-circular, large-aspect-ratio magnetic geometry
- frequencies fast relative to ion transit  $\omega\gg c_s/qR$  (justified)

None of the assumptions (except the last one) are generally justified for edge turbulence.

All of the assumptions are OK for the upcoming analysis.

## Rapid linear physics acts to cause electron adiabatic response



At frequencies lower than  $\sim$ parallel electron transit, we expect electron parallel force balance:

$$abla_{\parallel} n_e T_{e0} = n_0 e \nabla_{\parallel} \phi \Longrightarrow \tilde{n}_e / n_0 \approx e \tilde{\phi} / T_{e0}.$$

### Rapid linear physics acts to cause electron adiabatic response

Linear equations, with nonadiabatic electron response  $h_e \doteq n_e/n_0 - e\phi/T_{e0}$ 

$$egin{aligned} \partial_t n_e &+ \mathbf{v}_E \cdot 
abla n_0 &= rac{1}{e} 
abla_{\parallel} j_{\parallel} + rac{1}{e} \mathcal{K} \left( n_0 \mathrm{e} \phi - n_e T_{e0} 
ight) \ &rac{n_0 m_i}{B^2} \partial_t 
abla_{\perp}^2 \phi &= & 
abla_{\parallel} j_{\parallel} - \mathcal{K} \left( n_e T_{e0} 
ight) \ &\eta j_{\parallel} &= rac{T_{e0}}{n_0 \, e} 
abla_{\parallel} n_e - 
abla_{\parallel} \phi &= rac{T_{e0}}{e} 
abla_{\parallel} h_e \end{aligned}$$

If resistivity is small enough that parallel electron diffusion is rapid relative to drift wave frequencies, then we may neglect  $\mathbf{v}_E \cdot \nabla n_0$  and  $\mathcal{K}(\cdots)$ . Also take a single perpendicular mode  $\nabla_+^2 \rightarrow -k_+^2$ , then

$$\partial_t h_e \approx \frac{1}{n_0 e} \left( 1 + \frac{1}{k_\perp^2 \rho_s^2} \right) \nabla_{\parallel} j_{\parallel} = \frac{T_{e0}}{\eta n_0 e^2} \left( 1 + \frac{1}{k_\perp^2 \rho_s^2} \right) \nabla_{\parallel}^2 h_e$$

where  $T_{e0}/\eta n_0 e^2 = v_{te}^2/\nu_{ei}$  is a parallel electron diffusion coefficient.

At frequencies lower than  $(k_{\parallel}^2 v_{te}^2 / v_{ei} k_{\perp}^2 \rho_s^2)$ , we expect  $\tilde{n}_e / n_0 \approx e \tilde{\phi} / T_{e0}$ .

Parallel electron physics restricts free energy balance.

$$\begin{array}{c}
\gamma E_{\tilde{n}} \\
\downarrow \\
E_{n} \stackrel{:}{=} \frac{T_{e0}}{2n_{0}} n_{e}^{2}
\end{array}
\longleftrightarrow
\begin{array}{c}
E_{\sim} = \frac{1}{2} n_{0} m_{i} \tilde{v}_{E}^{2}
\longleftrightarrow
\begin{array}{c}
E_{z} = \frac{1}{2} n_{0} m_{i} \langle v_{E} \rangle^{2}
\end{array}$$

$$\downarrow \\
\downarrow \\
\text{Resistive dissipation} \\
\text{(weak for small } \eta)
\end{array}$$

$$\frac{E_{\sim}}{E_{\tilde{n}}} = \frac{\int d\mathcal{V} \tilde{v}_{E}^{2} / c_{s}^{2}}{\int d\mathcal{V} \left(\tilde{n}_{e}^{2} / n_{0}^{2}\right)} = \frac{\int d\mathcal{V} \left|\nabla_{\perp} \tilde{\phi}\right|^{2} / c_{s}^{2} B^{2}}{\int d\mathcal{V} \left(\tilde{n}_{e}^{2} / n_{0}^{2}\right)} \stackrel{\tilde{n}_{e}}{\stackrel{\tilde{n}_{e}}{=}} \frac{e^{\tilde{\phi}}}{n_{0}} k_{\perp}^{2} \rho_{s}^{2}$$

Reynolds stress must drain energy from  $(E_{\tilde{n}} + E_{\sim}) \gg E_{\sim}$ .

## Parallel electron physics restricts free energy balance.

Our equations nonlinearly conserve a free energy  $(E_n+E_{\sim}+E_z)$  for

$$E_n \doteq \frac{T_{e0}}{2n_0} \int d\mathcal{V} \, n_e^2; \quad E_{\sim} \doteq \frac{1}{2} n_0 m_i \int d\mathcal{V} \left[ (\tilde{v}_E^{\mathsf{x}})^2 + (\tilde{v}_E^{\mathsf{y}})^2 \right]; \quad E_z \doteq \frac{1}{2} n_0 m_i \int d\mathcal{V} \langle v_E \rangle^2$$
which evolve as  $\sigma_{e} = \int d\mathbf{v} \left[ T_{e0} - \mathbf{v} \right] \left[ T_{e0} - \mathbf{v} \right] \left[ T_{e0} - \mathbf{v} \right]$ 

which evolve as  $\partial_t E_n = \int \!\! \mathrm{d} \mathcal{V} \Big[ \frac{T_{e0}}{L_n} n_e v_E^{\times} - \frac{T_{e0}}{n_0 e} j_{\parallel} \nabla_{\parallel} n_e - T_{e0} \phi \mathcal{K} \left( n_e \right) \Big],$   $\partial_t E_{\sim} = \int \!\! \mathrm{d} \mathcal{V} \Big[ j_{\parallel} \nabla_{\parallel} \phi + T_{e0} \tilde{\phi} \mathcal{K} \left( n_e \right) - n_0 m_i (\tilde{v}_E^{\times} \tilde{v}_E^{\times}) \partial_x \langle v_E \rangle \Big],$   $\partial_t E_z = \int \!\! \mathrm{d} \mathcal{V} \left[ T_{e0} \left\langle \phi \right\rangle \mathcal{K} \left( n_e \right) + n_0 m_i (\tilde{v}_E^{\times} \tilde{v}_E^{\times}) \partial_x \langle v_E \rangle \Big],$   $\partial_t \left( E_n + E_{\sim} + E_z \right) = \int \!\! \mathrm{d} \mathcal{V} \Big[ \frac{T_{e0}}{L} n_e v_E^{\times} - \frac{T_{e0}}{L} j_{\parallel} \nabla_{\parallel} h_e \Big].$ 

Note that 
$$(T_{e0}/e)j_{\parallel}\nabla_{\parallel}h_{e}=\eta j_{\parallel}^{2}=(T_{e0}/e)^{2}(\nabla_{\parallel}h_{e})^{2}/\eta>0.$$

When  $\tilde{h}_e$  becomes small  $(\tilde{h}_e \ll \tilde{n}_e/n_0, e\tilde{\phi}/T_{e0})$ , then  $(T_{e0}/n_0e)j_{\parallel}\nabla_{\parallel}n_e \approx j_{\parallel}\nabla_{\parallel}\phi$ , so the red terms are approximately a conservative energy transfer.

## Implications for energy transfer in rapid L-H transition:

$$\begin{split} &\partial_{t}E_{n} \!=\! \int \!\!\mathrm{d}\mathcal{V} \Big[ \frac{T_{e0}}{L_{n}} n_{e} v_{E}^{\times} - \frac{T_{e0}}{n_{0}e} j_{\parallel} \nabla_{\parallel} n_{e} - T_{e0} \phi \mathcal{K} \left( n_{e} \right) \Big] \\ &\partial_{t}E_{\sim} \!=\! \int \!\!\mathrm{d}\mathcal{V} \Big[ j_{\parallel} \nabla_{\parallel} \phi + T_{e0} \tilde{\phi} \mathcal{K} \left( n_{e} \right) - n_{0} m_{i} (\tilde{v}_{E}^{\times} \tilde{v}_{E}^{y}) \partial_{x} \langle v_{E} \rangle \Big] \\ &\partial_{t}E_{z} \!=\! \int \!\!\mathrm{d}\mathcal{V} \left[ T_{e0} \left\langle \phi \right\rangle \mathcal{K} \left( n_{e} \right) + n_{0} m_{i} (\tilde{v}_{E}^{\times} \tilde{v}_{E}^{y}) \partial_{x} \langle v_{E} \rangle \right] \end{split}$$

Assume L-H transition is faster than growth rate  $\gamma$  but slow relative to electron parallel relaxation rate  $(k_{\parallel}^2 v_{te}^2 / v_{ei} k_{\perp}^2 \rho_s^2)$ , so  $\tilde{n}_e / n_0 \approx e \tilde{\phi} / T_{e0}$  thus

$$\frac{E_{\sim}}{E_{\tilde{n}}} = \frac{\int \! \mathrm{d}\mathcal{V} \left[ \left( \tilde{v}_E^{\mathsf{x}} \right)^2 + \left( \tilde{v}_E^{\mathsf{y}} \right)^2 \right] / c_s^2}{\int \! \mathrm{d}\mathcal{V} \left( \tilde{n}_e^2 / n_0^2 \right)} = \frac{\int \! \mathrm{d}\mathcal{V} \left[ \nabla_{\perp} \tilde{\phi} \right]^2 / B^2 c_s^2}{\int \! \mathrm{d}\mathcal{V} \left( \tilde{n}_e^2 / n_0^2 \right)} \sim k_{\perp}^2 \rho_s^2,$$

where  $k_{\perp}$  is roughly an rms-averaged perp wavenumber.

If 
$$\frac{\int \mathrm{d}\mathcal{V} \, n_0 m_i (\tilde{v}_E^x \tilde{v}_E^y) \partial_x \langle v_E \rangle}{E_{c_x}} \leq \max |\partial_x \langle v_E \rangle|$$

is slow relative to  $k_\parallel^2 v_{te}^2/(\nu_{ei} k_\perp^2 \rho_s^2)$ , then  $j_\parallel$  will keep  $E_\sim/E_{\tilde{n}} \sim k_\perp^2 \rho_s^2$  so that the Reynolds work must deplete  $(E_{\tilde{n}}+E_\sim)$  to extinguish the turbulence. Eddy shearing can increase  $E_\sim/E_{\tilde{n}} \propto k_\perp^2$ , but does not change  $(E_\sim+E_{\tilde{n}})$ .

For slow transition, energy transfer too weak for Waltz rule.

Turbulence suppression by energy transfer only for:

$$\gamma E_{\tilde{n}} < n_0 m_i \int d\mathcal{V} \left( \tilde{v}_E^x \tilde{v}_E^y \right) \partial_x \left\langle v_E \right\rangle \le \max \left| \partial_x \left\langle v_E \right\rangle \right| E_{\sim}, \text{ so for}$$

$$\max \left| \partial_x \left\langle v_E \right\rangle \right| > \gamma \frac{E_{\tilde{n}}}{E} \sim \frac{\gamma}{k^2 n^2} \gg \gamma$$

#### Implications for energy transfer in slow L-H transition:

$$\begin{split} &\partial_{t}E_{n} \!=\! \int \!\!\mathrm{d}\mathcal{V} \Big[ \frac{T_{e0}}{L_{n}} n_{e} v_{E}^{\times} - \frac{T_{e0}}{n_{0} e} j_{\parallel} \nabla_{\parallel} n_{e} - T_{e0} \phi \mathcal{K} \left( n_{e} \right) \Big] \\ &\partial_{t}E_{\sim} \!=\! \int \!\!\mathrm{d}\mathcal{V} \Big[ j_{\parallel} \nabla_{\parallel} \phi + T_{e0} \tilde{\phi} \mathcal{K} \left( n_{e} \right) - n_{0} m_{i} (\tilde{v}_{E}^{\times} \tilde{v}_{E}^{y}) \partial_{x} \langle v_{E} \rangle \Big] \\ &\partial_{t}E_{z} \!=\! \int \!\!\mathrm{d}\mathcal{V} \left[ T_{e0} \left\langle \phi \right\rangle \mathcal{K} \left( n_{e} \right) + n_{0} m_{i} (\tilde{v}_{E}^{\times} \tilde{v}_{E}^{y}) \partial_{x} \langle v_{E} \rangle \right] \end{split}$$

Assume now L-H transition is slower than both growth rate  $\gamma$  and electron parallel relaxation rate  $(k_{\parallel}^2 v_{te}^2 / \nu_{ei} k_{\perp}^2 \rho_s^2)$ .

Criterion for suppression by energy transfer to ZFs becomes stricter than

$$\gamma E_{\tilde{n}} \leq \int \mathrm{d}\mathcal{V} \, n_0 m_i (\tilde{v}_E^x \tilde{v}_E^y) \partial_x \langle v_E \rangle \leq E_{\sim} \max |\partial_x \, \langle v_E \rangle| \,,$$

a Hahm-Burrell-like formula modified by  $(k_{\perp}\rho_s)^2$ :

$$\max |\partial_x \langle v_E \rangle| \ge \gamma rac{E_{ ilde{n}}}{E_{\sim}} \sim rac{\gamma}{k_{\perp}^2 
ho_s^2}$$

For small  $k_{\perp}^2 \rho_s^2$ , this criterion is much stricter than the usual one, implying that this mechanism is probably not the dominant one.

Of course, flow shear may play other roles.

Assume now that energy transfer via Reynolds work is negligible, flow shear could still distort the spatial variation of the turbulence and thereby:

- $\blacktriangleright$  Decrease the effective growth rate  $\gamma$  by decorrelating growing modes,
- ▶ Increase dissipation due to transfer to high- $k_{\perp}$  by eddy shearing

Or maybe the transition is even triggered by something else entirely?

#### Conclusions

In a popular description of the L-H transition, energy transfer to the mean flows directly depletes turbulence fluctuation energy, resulting in suppression of the turbulence and a corresponding transport bifurcation. However, electron parallel force balance couples nonzonal velocity fluctuations with electron pressure fluctuations on rapid timescales, comparable with the electron transit time. For this reason, energy in the nonzonal velocity stays in a fairly fixed ratio to electron thermal free energy, at least for frequency scales much slower than electron transit. In order for direct depletion of the energy in turbulent fluctuations to cause the L-H transition, energy transfer via Reynolds stress must therefore drain enough energy to significantly reduce the sum of the free energy in nonzonal velocities and electron pressure fluctuations. At low  $k_{\perp}$ , the electron thermal free energy is much larger than the energy in nonzonal velocities, posing a stark challenge for this model of the L-H transition.

This work is part of a collaboration with Ahmed Diallo, Stewart Zweben, and Santanu Banerjee, doing experimental investigation of the L-H transition on NSTX with gas puff imaging (GPI).