

# Recent results from LTX and near-term plans

Presented by Dick Majeski

L. Berzak, S. Gershman, E. Granstedt, C. M. Jacobson, R. Kaita, T. Kozub,  
B. LeBlanc, N. Logan, D. P. Lundberg, M. Lucia, C. Skinner, K. Snieckus,  
D. Sobers, J. Timberlake, L. Zakharov, *PPPL*

T. Biewer, T. Gray, R. Maingi, *ORNL*

K. Tritz, *Johns Hopkins University*

C. E. Thomas, *Third Dimension, Inc.*


# Outline

---



- ◆ LTX overview
  - Shell and heater systems
  - Fueling systems
  - Recycling diagnostics
  - 2010 lithium evaporation system
- ◆ Results with evaporated coatings
  - Cold walls
  - Hot walls and discussion
- ◆ Near-term plans


# LTX has a full, 5 m<sup>2</sup> heated, conformal wall



LTX

Parameter	CDX-U	LTX
Major radius	0.34 m	0.4 m
Minor radius	0.22 m	0.26 m
Toroidal field	0.21 T	0.34 T
Plasma current	100 kA	400 kA
Current flattop	5 ms	>100 ms
Ohmic flux	30 mV-s	160 mV-s (centerstack maximum: 225 mV-s)
Wall temp.	20 °C	400 °C now, ~ 600 °C future

# Robust operation of LTX heaters to 300 °C demonstrated




Heater cold ends

Swagelok + Wilson seal


Ceramic break

External heater leads

Surface coated by evaporation.




Support legs





◆ Detail of full shell support structure

# Recycling source being replaced by active fueling

- ◆ Molecular cluster injector for LTX
  - Precooled (82K) gas condenses through nozzle exhaust
    - Forms clusters
  - Less expansion of jet
  - High fueling capability
  - Millisecond response
- ◆ Combined with existing supersonic gas injector



Supersonic Gas Injector





Molecular Cluster Injector


➔ Talk by D. Lundberg, Session IIB

# Recycling measurements employ Lyman- $\alpha$ arrays


- ◆ Lyman- $\alpha$  array viewing shell high-field (inner) side



- ◆ View of shell low-field (outboard) side through tangential port (array developed by K. Tritz, JHU)




- ◆ View of lower molybdenum limiter in lower shell




→ Talk by E. Granstedt, Session IIB

# New lithium coating systems developed for LTX



Evaporator (1 of 2) with linear motion stage mounted on LTX




$Y_2O_3$  crucible, Ta heater  
➤ Tested to 700 °C

- ◆ Two evaporators installed
- ◆ LTX lithium experiments have begun
- ◆ Total of 10 g evaporated onto walls in first round
  - 44g total lithium evaporated in 2010
  - Sufficient for a 4 micron coating of the entire shell

# Crucibles and heaters recycled successfully

LTX





- ◆ Cleanup relatively straightforward
- ◆ No significant issues with yttria crucibles after 600C operations
  - Lithium did not wet the crucible
  - Thermocouple wetting provided an escape route



# Current LTX status


LTX

- ◆ (Almost) overhead fisheye view of LTX




- ◆ Plasma current ~70 kA, shot duration ~20 msec
  - Thomson:  $T_e \sim 50 - 150$  eV
- ◆ Shells routinely heated to 300 C for bakeout
- ◆ Operated with lithium coatings October – December 2010
- ◆ Presently vented for maintenance, upgrades: May pumpdown

# Lithium initially evaporated into helium glow




Glow probe head  
>Lithium-dominated discharge  
>Working gas was helium




RGA trace indicating lithium gettering of water  
>Trace is dominated by liberated hydrogen

- ◆ Lithium introduced by evaporation from yttria crucibles at 550 C
- ◆ 5 gram load per crucible, 2 crucibles, 1.2 g evaporated in first run

# Lithium wall conditioning produced immediate effect on the discharge



Plasma current comparison




Pressure evolution

- ◆ First lithium operation shown – cold shell
- ◆ Lithium glow preceded by helium glow with hot (250C) shell for preconditioning
- ◆ Discharge current, duration significantly increased after only a few hours of operation following Li glow
- ◆ Pressure history demonstrates reduction in recycling

# LTX has now been operated with a lithium-coated 300 °C shell



- ◆ First full high temperature, high Z wall operation of a tokamak
  - Lithium evaporate into 5 mTorr helium fill to disperse coating





(Warm) cluster injector system, wall puffer employed for fueling with cold lithium walls

- ◆ Hot (300 °C) shell with thin lithium coatings does *not* exhibit a significant reduction in recycling
  - “Liquid” lithium is impurity-dominated
  - Relevant to NSTX operation with heated LLD?

# Shell interior at 300 °C after 4 g lithium deposition

LTX



- ◆ Deposition rate  $\sim 0.75$  g/hour/evaporator; 3 hour evaporation
  - Evaporate into 5 mTorr helium to distribute lithium
  - Est. 1.6 micron average deposition layer
- ◆ Lithium coating darkens rapidly
  - Indicative of reactions with background gases
- ◆ No visual evidence of metallic surface

# Discussion of hot wall results

---



- ◆ Partial pressure of water during cold wall lithium evaporation was  $\sim 5 \times 10^{-9}$  Torr
- ◆ Partial pressure of water during the hot wall experiment was  $\sim 2 \times 10^{-8}$  Torr
- ◆ With cold walls, improved discharges were obtained for  $\sim 48$  hours
- ◆ With hot walls, no improved discharges were observed
  - Delay between termination of coating and tokamak operations was 1 hour, 15 minutes
  - If the only factor affecting the condition of the lithium coating was background water pressure, coating should have been active for  $\sim 12$  hours
- ◆ Therefore, hot coating passivated more quickly than can be accounted for by background water pressure
- ◆ Suspect segregation of oxygen, other impurities to the surface was responsible for rapid passivation


– C. Skinner, poster session IIB

# LTX and CDX-U fueling




- ◆ Fueling requirements for LTX are approaching CDX-U requirements for low recycling operation
  - LTX: similar shot duration
  - Lower plasma current, density

Total fueling  
⇒including  
prefill



# Loop voltage comparison indicates modestly improved discharge performance with cold wall coatings

LTX



- ◆ Preliminary result (just a few discharges from LTX)
- ◆ Require more discharges, full confinement assessment



# Near-term (2011) plans


---



- ◆ Improve vacuum conditions in LTX
  - Adding vacuum vessel bakeout to 120 C
  - Vessel will be cooled during tokamak operations with hot shell
- ◆ Increase shell bakeout temperature to 400 C
- ◆ Add water pumping
  - Installing two lithium getter pumps
  - Pumping speed for each unit estimated at 2500 L/sec
  - Each pump will employ a heated lithium crucible and a large wall area for lithium deposition
- ◆ Summer 2011: begin operations with liquid lithium fills in both lower shells
- ◆ Preliminary assessment of confinement with partial liquid lithium walls later this year

# Lower shells designed for liquid lithium pools

LTX



- ◆ Lower shells have welded stainless steel lips to retain lithium
- ◆ Double molybdenum limiters are designed to wick lithium
  - Molybdenum limiters extend 2 mm above the stainless steel retention lips