

An overview of the HIT research program and its implications for magnetic fusion energy

D.A. Sutherland, T.R. Jarboe, B.A. Nelson, A.C. Hossack, K.D. Morgan, C. Hansen, C.J. Everson, T. Benedett

University of Washington, AERB Room 120, Box 352250, Seattle, WA, 98105, USA

Lead-author e-mail: das1990@uw.edu

The HIT research group reports evidence of pressure confinement in sustained spheromak configurations, quantitative agreement with Hall-MHD simulations, and a possible new pathway towards economical magnetic fusion energy. In HIT-SI ($R_o = 0.34$ m, $a = 0.2$ m), two inductive helicity injectors oscillating 90° out of phase, continually drive edge currents and impose magnetic perturbations that provide sustainment via imposed-dynamo current drive (IDCD).¹ Experimental results² indicate the sustainment of a spheromak configuration without gross confinement-degrading instabilities that have plagued spheromaks previously;³ an example derivation of the IDCD mechanism is provided.⁴ The level of quantitative agreement between the experiment and Hall-MHD simulations with NIMROD and PSI-TET is presented, along with suggestions of next steps to improve agreement. Lastly, an IDCD-driven spheromak reactor concept (the dynamak) is presented that indicates cost-competitiveness with conventional energy sources.⁵ The dynamak utilizes a molten salt (FLiBe) blanket system for first wall cooling, neutron moderation and tritium breeding. A tritium breeding ratio (TBR) of greater than 1.1 has been calculated using a Monte Carlo N-Particle (MCNP5) neutron transport simulation. High temperature superconducting tapes (YBCO) are used for the equilibrium coil set, though more conventional low-temperature superconductors could also be used. The limiting equilibrium coil set lifetime is at least thirty full-power years. The primary FLiBe loop is coupled to a supercritical carbon dioxide Brayton cycle due to attractive economics and high thermal efficiencies. With these advancements, an electrical output of 1000 MW is produced from a thermal output of 2486 MW, yielding an overall plant efficiency of approximately 40%. The overnight capital cost of this 1 GWe power plant is estimated to be \$2.7 billion in 2013 USD.

¹ T.R. Jarboe, et al., *Nuc. Fus.* **52** (2012) 8, 083017.

² B.S. Victor, et al., *Phys. Plasmas* **21** (2014) 082504.

³ B. Hudson, et al., *Phys. Plasmas* **15** (2008) 056112.

⁴ T.R. Jarboe, et al., *Phys. Plasmas* **22** (2015) 072503.

⁵ D.A. Sutherland, et al., *Fus. Eng. Des.* **89** (2014) 4, 412-425