

NSTX-U is sponsored by the U.S. Department of Energy Office of Science Fusion Energy Sciences

Update on Activities and Action Items for PFCR Working Group M.L. Reinke

PFCR-WG B-252 5/24/2017







Goals of this Meeting

review in-progress MEMOs and open ACTION ITEMS

 introduce draft revision of R18-1 milestone and how it maps to the PFCR-WG charges

-further discussion tomorrow-AM



PFC Requirements Working Group Charges

- 1. define which (additional) parameters need to be specified in an updated requirements document for the NSTX-U PFCs
- 2. facilitate generation of updated requirements utilizing:
 - a) available reduced models, empirical scalings, boundary simulations
 - b) ultimately, a validated model for specifying heat loads to all plasma facing components for arbitrary NSTX-U scenarios
- 3. in preparation for operations, develop:
 - a) instrumentation plan for intra and inter-shot PFC monitoring
 - b) a reduced model for heat loading for pre-shot planning
 - c) guidance on how to best integrate monitoring with operations
 - d) control, diagnostic requirements for real-time heat-flux control
- 4. work closely with engineers and analysts to develop and implement requirements

http://nstx-u.pppl.gov/program/working-groups/pfc-requirements-working-group



Review On-Going Work

- for people present, please summarize what's being worked on and progress being made
 - -<u>MEMOs</u>
 - -<u>ACTION ITEMS</u>



New Work?

• likely going to be some items generated by the TSG meeting presentations/MEMOs from this morning...



Revised R18-1 Milestone

FY18-1: Develop and Benchmark Operations-Focused Reduced Heat Flux and Thermo-Mechanical Models for use in PFC Monitoring

The NSTX-U Recovery Project will deploy new plasma facing components (PFCs) to meet updated heat exhaust requirements driven by a narrower scrape-off-layer width, increased heating power and longer pulse durations relative to NSTX. Inter-shot monitoring or intra-shot control of heat flux to PFCs is anticipated for a range NSTX-U operating space, necessitating reduced models that can be run between shots or even in real-time. Monitoring requires a reliable instrumentation suite which can support or contradict model predictions and confirm PFC integrity. The goals of this milestone will be accomplished in three major components: 1) Develop tools for pre-shot planning and confirmation of post-shot PFC thermal observations which use reduced models to predict timeevolving heat fluxes to shaped PFCs and estimate distances from engineering limits. Assess additional effort needed for implementation of reduced models in PCS. 2) Where feasible, benchmark reduced models against boundary physics (e.g. SOLPS, UEDGE) and finite element analysis (e.g. ANSYS) tools, and validate using experimental data from relevant tokamaks and results from FY18-2. 3) Evaluate examples of discrete monitoring systems that are sufficient to capture the evolution of the PFCs relative to engineering limits. Compare the ability for different techniques (e.g. thermocouples vs. imaging) and technologies (e.g. near vs. long-wave infrared cameras) to achieve NSTX-U PFC monitoring objectives.



Revised R18-1 Milestone

FY18-1: Develop and Benchmark Operations-Focused Reduced Heat Flux and Thermo-Mechanical Models for use in PFC Monitoring

The NSTX-U Recovery Project will deploy new plasma facing components (PFCs) to meet updated heat exhaust requirements driven by a narrower scrape-off-layer width, increased heating power and longer pulse durations relative to NSTX. Inter-shot monitoring or intra-shot control of heat flux to PFCs is anticipated for a range NSTX-U operating space, necessitating reduced models that can be run between shots or even in realtime. Monitoring requires a reliable instrumentation suite which can support or contradict model predictions and confirm PFC integrity. The goals of this milestone will be accomplished in three major components: 1) Develop tools for pre-shot planning and confirmation of post-shot PFC thermal observations which use reduced models to predict time-evolving heat fluxes to shaped PFCs and estimate distances from engineering limits. Assess additional effort needed for implementation of reduced models in PCS. 2) Where feasible, benchmark reduced models against boundary physics (e.g. SOLPS, UEDGE) and finite element analysis (e.g. ANSYS) tools, and validate using experimental data from relevant tokamaks and results from FY18-2. 3) Evaluate examples of discrete monitoring systems that are sufficient to capture the evolution of the PFCs relative to engineering limits. Compare the ability for different techniques (e.g. thermocouples vs. imaging) and technologies (e.g. near vs. longwave infrared cameras) to achieve NSTX-U PFC monitoring objectives.

- 1. define which (additional) parameters need to be specified in an updated requirements document for the NSTX-U PFCs
- 2. facilitate generation of updated requirements utilizing:
 - a) available reduced models, empirical scalings, boundary simulations
 - b) ultimately, a validated model for specifying heat loads to all plasma facing components for arbitrary NSTX-U scenarios
- 3. in preparation for operations, develop:
 - a) instrumentation plan for intra and inter-shot PFC monitoring
 - b) a reduced model for heat loading for pre-shot planning
 - c) guidance on how to best integrate monitoring with operations
 - d) control, diagnostic requirements for real-time heatflux control
- 4. work closely with engineers and analysts to develop and implement requirements