

**Princeton Plasma Physics Laboratory  
NSTX Experimental Proposal**

Characterization of the divertor heat flux width and the mid-plane SOL widths

**OP-XP-815**

Revision:

Effective Date: **03/21/08**  
*(Approval date unless otherwise stipulated)*

Expiration Date:  
*(2 yrs. unless otherwise stipulated)*

**PROPOSAL APPROVALS**

**Responsible Author: J-W. Ahn, J. Boedo, R. Maingi, R. Maqueda, and S. Zweben**

Date 03/21/08

**ATI – ET Group Leader: V. Soukhanovskii**

Date

**RLM - Run Coordinator: M. Bell (R. Raman)**

Date

**Responsible Division: Experimental Research Operations**

**Chit Review Board** (designated by Run Coordinator)

**MINOR MODIFICATIONS** (Approved by Experimental Research Operations)

# NSTX EXPERIMENTAL PROPOSAL

TITLE: Characterization of the divertor heat flux width  
and the mid-plane SOL widths

No. **OP-XP-815**

AUTHORS: J-W. Ahn, J. Boedo, R. Maingi

DATE: 03/27/08

---

## 1. Overview of planned experiment

This experiment aims to measure SOL plasma profiles ( $T_e$ ,  $n_e$ ,  $j_{\text{sat}}$ , and  $q_{\text{target}}$ ) with operation parameters (eg,  $I_p$ ,  $n_{\text{bar}}$ ,  $B_t$ , and power) scanned. The  $T_e$ ,  $n_e$ , and  $j_{\text{sat}}$  profiles are measured by the mid-plane fast probe and the  $q_{\text{target}}$  profile is measured by the divertor IR camera. Various other diagnostics (GPI, FIRETIP, USXR, fast visible camera, etc) will also measure blob characteristics in the SOL plasma. All the measured profiles will be flux mapped to the mid-plane for comparison. The goal is to find out 1) the relation between various decay lengths at the target and at the mid-plane, 2) the dependence of SOL widths on the operation parameters and the development of SOL width scaling law for both near and far SOLs, and 3) the relationship between SOL widths and the blob characteristics.

## 2. Theoretical/ empirical justification

The electron temperature and heat flux SOL widths,  $\lambda_{T_e}$  and  $\lambda_q$  respectively, have a conventional relation of  $\lambda_{T_e} = 7/2\lambda_q$ , assuming a dominant parallel electron heat conduction and a simple exponential function for the  $T_e$  and  $q_{\text{target}}$  profiles. However, it has been observed that the profiles have a long tail in the far SOL and this can be approximated by introducing an offset value in the exponential function, ie  $a = a_0 + a_1 \exp\left(-\frac{R-R_{\text{sep}}}{\lambda_a}\right)$ . If we use the offset exponential function for both  $T_e$  and  $q$  profiles and apply it to the parallel electron heat conduction equation in the near SOL, we obtain a new relation between  $\lambda_{T_e}$  and  $\lambda_q$ ,

$$\lambda_{T_{e,u}} = \frac{7}{2} \lambda_q \left( \frac{T_{e,u} - T_{e0}}{T_{e,u} - C q_0 T_{e,u}^{-5/2}} \right)$$

, where  $C = \frac{7 L_c}{2 \kappa_e}$ ,  $T_{e0}$  and  $q_0$  are the offset  $T_e$  and  $q$  values, and  $\kappa_e$  is the electron conduction coefficient. The measured value of  $\lambda_{T_e}/\lambda_q$  differs from the new prediction by 17%, compared to the 26% difference from the conventional prediction. The use of offset temperature and heat flux values,  $T_{e0}$  and  $q_0$ , in the parallel e-conduction equation can be interpreted as a representation of relatively strong perpendicular heat transport.

On the other hand, the measured far SOL widths do not follow the expected relation neither for the sheath-limited ( $\lambda_q^{-1} = \lambda_n^{-1} + 3/2 \lambda_T^{-1}$ ) nor the conduction-limited ( $\lambda_{T_e} = 7/2\lambda_q$ ) regime. While the measured  $\lambda_q$  is 9.8cm, the expected value is  $2.6 < \lambda_q < 4.0$  cm (sheath-limited regime) and  $\lambda_q = 3.3$  cm (conduction-limited regime). One of the possibilities under consideration to explain the discrepancy is the long ion heat flux decay length.

The scaling of SOL widths with operation parameters ( $I_p$ ,  $n_{\text{bar}}$ ,  $B_T$ , power, etc) is important for the extrapolation to the future machine such as NHTX in two ways; the near SOL scaling and the far SOL scaling. The near SOL scaling is important to estimate heat flux onto the divertor target and

therefore to evaluate power handling capabilities. The far SOL scaling is also important to estimate heat and particle flux onto the 1<sup>st</sup> wall and therefore to evaluate its interaction with the wall.

As for the near SOL scaling, the IR heat flux data has been already scaled with  $I_p$  and power [1] and the fast probe  $T_e$  and  $n_e$  profiles showed dependence on  $I_p$ , nebar, and power. However, the size of current dataset is limited and scaling laws have not been derived. The derived experimental scaling will be supplemented by the best fitting theoretical models to be identified by comparison of experimental data with analytic models. Currently the most comprehensive analytic SOL models are provided by a reference by J.W.Connor and G.F.Counsell [2]. This will provide useful information for the extrapolation of NSTX near SOL width data to NHTX.

The long tail of plasma profiles in the far SOL can be the result of intermittent perpendicular heat and particle transport, which is a subject of intense investigation in the boundary physics community. The degree of intermittent perpendicular transport can be characterized by the ‘offset’ value or by the decay length of a far SOL profile. The theory of intermittent perpendicular transport is still being developed and there is a need to develop empirical scalings to confirm the dependence of this transport on the operation parameters. This will provide an experimental basis to the theoretical investigation of the intermittent transport.

The last task of this experiment is to find a relationship between SOL widths and the blob characteristics. Blobs are expected to play an important role in the intermittent perpendicular particle and heat transport. Characteristics of blob such as fluctuation characteristics, blob velocities and directions, and the number of filaments, etc will be investigated in the relation with SOL widths as a function of operation parameters. This may provide useful input to the theoretical blob models currently under development (eg, at Lodestar).

[1] R. Maingi, C.E. Bush, R. Kaita, H.W. Kugel, A.L. Roquemore, S.F. Paul, V.A. Soukhanovskii, and the NSTX team, et. al., *Journal of Nuclear Materials* **363-365** (2007) 196

[2] J. W. Connor, G. F. Counsell, et. al., *Nuclear Fusion* **39** (1999) 169

### 3. Experimental run plan (in the order of priority)

- |  |
|--|
| <ul style="list-style-type: none"> <li>§ Derate NBI src. C to 1MW<br/>NBI order: 2MW, 80-300ms (A); 2MW, 140-250 (B); 1MW, 300-500ms (C)</li> <li>§ Plunge probe at 350ms</li> <li>§ Plasma configuration: LSN, Drsep~3cm, <math>\kappa=2.0</math>, <math>\delta=0.45</math></li> <li>§ Timing for other diagnostics: GPI, IR, FIReTIP, etc<br/>to be aligned with probe plunge time, ie 300-500ms as planned</li> <li>§ Density scan: plunge probe at 2 different times<br/>roughly at 300ms (<math>3.0e19</math>) and 400ms (<math>5.0e19</math>)</li> </ul> |
|--|
- § Establish baseline shot. Start from repeating shot #125065  
1.0MA, 0.55T, 1MW NBI (4 shots)
  - §  $I_p$  scan at approximately fixed  $q_{95}$ 
    - 0.7MA, 0.385T, 1MW (4)
    - 0.8MA, 0.45T, 1MW (2)
    - 0.9MA, 0.495T, 1MW (2)
  - § Density scan

0.8MA, 0.45T, 1MW, 3.0e19 (4)

0.8MA, 0.45T, 1MW, 5.0e19 (4)

If time permits,

§ Power scan

0.8MA, 0.45T, 0MW NBI (4)

§ Bt scan at fixed Ip

0.8 MA, 0.55 T (4) ; 0.8 MA, 0.35 T (4)

#### **4. Required machine, NBI, RF, CHI and diagnostic capabilities**

This XP requires a fully operational NBI system. We desire HeGDC between shots of ~ 6.5 minutes for a 12.5 minute repetition rate.

#### **5. Planned analysis**

The SOL widths will be analyzed from the data obtained from the fast probe and the IR camera, and relationships between the SOL widths will be investigated. The SOL widths data will be scaled with operation parameters to derive the scaling law and will be compared with analytic cross-field transport models. The GPI data will be analyzed to yield blob characteristics and this will be compared with SOL widths data to find relationships. EFIT will be necessary for the flux mapping of the profiles to the mid-plane.

#### **6. Planned publication of results**

Data and analysis for the relation of SOL widths will be presented at the PSI conference in May 2008 and be published in J. Nucl. Materials in 2009. SOL width scaling work will be published in an appropriate refereed journal.

# PHYSICS OPERATIONS REQUEST

TITLE: Characterization of the divertor heat flux width and the mid-plane SOL widths No. **OP-XP-815**

AUTHORS: J-W. Ahn, J. Boedo, R. Maingi, R. Maqueda, S. Zweben DATE: 03/27/08

Machine conditions (specify ranges as appropriate)

$I_{TF}$  (kA): **63** Flat top start/stop (s):

$I_p$  (MA): **0.7-1.0** Flat top start/stop (s): **0.15/1.0 (max)**

Configuration: **LSN**

Outer gap (m): **10cm** Inner gap (m): **5-10cm**

Elongation  $\kappa$ : **2.0** Upper/lower triangularity  $\delta$ : **0.45**

Z position (m): **0.0**

Gas Species: **D** Injector(s): Inner wall Mid-plane

NBI Species: **D** Sources: **A/B/C** Voltage (kV): Duration (s): **<1sec**

ICRF Power (MW): Phasing: Duration (s):

CHI: **On / Off** Bank capacitance (mF):

LITER: **On / Off**

*Either:* List previous shot numbers for setup: **125065 (LSN)**

*Or:* Sketch the desired time profiles, including inner and outer gaps,  $\kappa$ ,  $\delta$ , heating, fuelling, etc. as appropriate. Accurately label the sketch with times and values.





## DIAGNOSTIC CHECKLIST

TITLE: Characterization of the divertor heat flux width and the mid-plane SOL widths

No. **OP-XP-815**

AUTHORS: J-W. Ahn, J. Boedo, R. Maingi, R. Maqueda, S. Zweben

DATE: 03/27/08

*Note special diagnostic requirements in Sec. 4*

Diagnostic	Need	Want
Bolometer – tangential array	√	
Bolometer – divertor		√
CHERS – toroidal	√	
CHERS – poloidal		√
Divertor fast camera	√	
Dust detector		
EBW radiometers		
Edge deposition monitors		
Edge neutral density diag.	√	
Edge pressure gauges	√	
Edge rotation diagnostic	√	
Fast ion D <sub>α</sub> - FIDA		
Fast lost ion probes - IFLIP		√
Fast lost ion probes - SFLIP		√
Filterscopes	√	
FIReTIP	√	
Gas puff imaging	√	
H $\alpha$ camera - 1D	√	
High-k scattering		√
Infrared cameras	√	
Interferometer - 1 mm		
Langmuir probes – divertor	√	
Langmuir probes – BEaP		√
Langmuir probes – RF ant.		
Magnetics – Diamagnetism	√	
Magnetics – Flux loops	√	
Magnetics – Locked modes	√	
Magnetics – Pickup coils	√	
Magnetics – Rogowski coils	√	
Magnetics – Halo currents		√
Magnetics – RWM sensors		√
Mirnov coils – high f.	√	
Mirnov coils – poloidal array		√
Mirnov coils – toroidal array		√
Mirnov coils – 3-axis proto.		√

*Note special diagnostic requirements in Sec. 4*

Diagnostic	Need	Want
MSE		√
NPA – ExB scanning		√
NPA – solid state		
Neutron measurements		
Plasma TV		√
Reciprocating probe	√	
Reflectometer – 65GHz		√
Reflectometer – correlation		√
Reflectometer – FM/CW		√
Reflectometer – fixed f		√
Reflectometer – SOL		√
RF edge probes		
Spectrometer – SPRED		√
Spectrometer – VIPS		√
SWIFT – 2D flow		√
Thomson scattering	√	
Ultrasoft X-ray arrays	√	
Ultrasoft X-rays – bicolor		√
Ultrasoft X-rays – TG spectr.		√
Visible bremsstrahlung det.		√
X-ray crystal spectrom. - H		
X-ray crystal spectrom. - V		
X-ray fast pinhole camera		
X-ray spectrometer - XEUS		