

Btf (kG)	Itf (Amp)	Tstart (sec)	dTrise (pedestal) (sec)	dT (pedestal) (sec)	dTrise (pedestal-to- flat) (sec)	dTflat (sec)	dTfall (sec)	Σ Time Duration (sec)	Tend (sec)
6	71167	-0.750	0.023	0.145	0.605	0.571	0.252	1.573	0.823
5.75	68201	-0.750	0.023	0.204	0.546	0.691	0.244	1.685	0.935
5.5	65236	-0.750	0.023	0.255	0.495	0.817	0.236	1.803	1.053
5.25	62271	-0.750	0.023	0.301	0.449	0.952	0.228	1.930	1.180
5	59306	-0.750	0.023	0.342	0.408	1.101	0.219	2.070	1.320
4.75	56340	-0.750	0.023	0.379	0.371	1.268	0.211	2.228	1.478
4.5	53375	-0.750	0.023	0.413	0.337	1.457	0.202	2.409	1.659
4.25	50410	-0.750	0.023	0.444	0.306	1.675	0.193	2.618	1.868
4	47444	-0.750	0.023	0.473	0.277	1.931	0.184	2.865	2.115
3.75	44479	-0.750	0.023	0.500	0.250	2.235	0.175	3.160	2.410
3.5	41514	-0.750	0.023	0.525	0.225	2.603	0.165	3.518	2.768
3.25	38549	-0.750	0.023	0.549	0.201	3.054	0.155	3.959	3.209
3	35583	-0.750	0.023	0.571	0.179	3.619	0.145	4.514	3.764

Notes:

- 1) Pedestal durations are <300mS for Bt> 5.25kG due to start time constraint; measurements under these conditions will be distorted due to settling effects
- 2) SOP averaging begins 50mS prior to TF ramp or at t=-0.5 whichever comes first
- 3) TF overtime set at 3.0s, allows full available flat top at Bt>3.5T