

**Princeton Plasma Physics Laboratory  
NSTX Experimental Proposal**

**Title: Modifications to early discharge evolution to reduce impurity content**

**OP-XP-1005**

Revision:

Effective Date: **3/22/2010**  
*(Approval date unless otherwise stipulated)*

Expiration Date: **3/22/2012**  
*(2 yrs. unless otherwise stipulated)*

**PROPOSAL APPROVALS**

**Responsible Author: J. Menard, S. Gerhardt, J. Canik, R. Maingi**

Date **3/22/2010**

**ATI – ET Group Leader: S. Gerhardt**

Date

**RLM - Run Coordinator: E. Fredrickson**

Date

**Responsible Division: Experimental Research Operations**

**RESTRICTIONS or MINOR MODIFICATIONS**

(Approved by Experimental Research Operations)

# NSTX EXPERIMENTAL PROPOSAL

TITLE: **Modifications to early discharge evolution to reduce impurity content** No. **OP-XP-1005**

AUTHORS: **J. Menard, S. Gerhardt, J. Canik, R. Maingi** DATE: **3/22/1010**

## 1. Overview of planned experiment

The goal of the proposed experiment is to reduce the accumulation of low-Z and high-Z impurities in LITER/LLD ELM-free H-mode plasmas by reducing the impurity influx and confinement during the early H-mode and current ramp-up phase of the discharge. Variations in magnetic balance and early ELM triggering with 3D fields will be utilized to modify the early and late impurity content.

## 2. Theoretical/ empirical justification

Previous operation with LITER led to favorable ELM-free H-mode operation with very high confinement. However, unfavorable confinement of C and metallic impurities has also been observed often leading to high radiation and/or H→L back-transitions after  $t=0.7-1s$ . In 2009, shifting the plasma vertically in the unfavorable  $\nabla B$  drift direction during the current ramp-up phase ( $t=80-200ms$ ) was observed to reduce the early and late carbon accumulation. Carbon density profile evolution data indicates that C is confined near the plasma edge until approximately  $t=0.4s$ , after which it is transported inward. Thus, reduction of the edge C density in the first 200-300ms using 3D fields for ELM triggering could also be effective for reducing the late C accumulation.

## 3. Experimental run plan

- A. Reproduce long-pulse scenario with LITER/LLD which is ELM-free and with strong C impurity accumulation in edge – reference shot is 136027 (3 shots)
- B. Scan magnetic balance direction (DRSEP) before, during, after early H-mode, assess impact on early impurity accumulation to determine discharge phase most responsible for C accumulation:
  - a. During  $t=0.05-0.4s$ , scan DRSEP = -2, -1, 0, 1, 2 cm (constant in time) (8 shots)
    - i. Add early NBI power as needed to trigger/retain early H-mode during ramp-up
- C. In conditions w/ minimized C content, add  $n=3$  RMP pulses during ramp-up + early flat-top, i.e.  $t=100-300ms$  (i.e. attempt to “clip” the density ears) (9 to 18 shots)
  - a. Optimize amplitude, duty-factor, start-time to reduce C during ramp
    - i. Use 50Hz (20ms period), start 50ms before, during, after early H-mode, off at 0.3s
    - ii. 1, 1.5, 2kA and  $\Delta t = 8ms$  to 4ms
  - b. Modify amplitude/duration to minimize early rotation damping and MHD instability
- D. After above scans, for case with lowest C content, scan late DRSEP to assess changes in late C accumulation (DRSEP ramp between 0.3-0.5s) (6 shots)

#### **4. Required machine, NBI, RF, CHI and diagnostic capabilities**

See Physics Operations Request

#### **5. Planned analysis**

MSE LRDFIT + TRANSP + NCLASS to model neoclassical impurity transport.

#### **6. Planned publication of results**

Results will be published in Nuclear Fusion, Phys. Plasmas, or possibly Phys. Rev. Lett. within 1 year.

# PHYSICS OPERATIONS REQUEST

TITLE: **Modifications to early discharge evolution to reduce impurity content** No. **OP-XP-1005**

AUTHORS: **J. Menard, S. Gerhardt, J. Canik, R. Maingi** DATE: **3/22/1010**

## Brief description of the most important operational plasma conditions required:

- DRSEP scans will be performed, so some discharge and/or control development/optimization will be required for this XP.
- Reproducible 800kA NBI discharge (or best available fiducial) with early H-mode.
- Implementation of early EF correction could be beneficial if early RMP is observed to reduce the early rotation leading to increased mode locking.

**Previous shot(s) which can be repeated: 136027 or 135999 or fiducial**

**Previous shot(s) which can be modified: (see above)**

**Machine conditions** (*specify ranges as appropriate, strike out inapplicable cases*)

$I_{TF}$  (kA): **53kA** Flattop start/stop (s): **-0.040/1.4s**

$I_p$  (MA): **0.8MA** Flattop start/stop (s): **0.15-1.2s**

Configuration: **LSN, balanced DND, and USN will be utilized (DRSEP = -2 to 2cm)**

Equilibrium Control: **Isoflux** (rtEFIT)

Outer gap (m): **see reference** Inner gap (m): Z position (m):

Elongation: Triangularity (U/L): OSP radius (m):

Gas Species: **D** Injector(s): **see reference shot**

NBI Species: **D** Voltage (kV) **A: 90 B: 90 C: 70** Duration (s): **1.2s**

ICRF Power (MW): **0** Phase between straps ( $^{\circ}$ ): Duration (s):

CHI: **Off** Bank capacitance (mF):

LITERs: **On** Total deposition rate (mg/min): **20mg/min**

LLD: Temperature ( $^{\circ}$ C): **warm (if warm LLD provides reproducible pumping)**

EFC coils: **On** Configuration: **Odd**

## DIAGNOSTIC CHECKLIST

**TITLE: Modifications to early discharge evolution to  
reduce impurity content**

**No. OP-XP-1005**

**AUTHORS: J. Menard, S. Gerhardt, J. Canik, R. Maingi DATE: 3/22/2010**

*Note special diagnostic requirements in Sec. 4*

Diagnostic	Need	Want
Beam Emission Spectroscopy		X
Bolometer – divertor	X	
Bolometer – midplane array		X
CHERS – poloidal		X
CHERS – toroidal	X	
Dust detector		X
Edge deposition monitors		X
Edge neutral density diag.		X
Edge pressure gauges		X
Edge rotation diagnostic		X
Fast cameras – divertor/LLD	X	
Fast ion D <sub>α</sub> - FIDA		X
Fast lost ion probes - IFLIP		X
Fast lost ion probes - SFLIP		X
Filterscopes	X	
FIReTIP		X
Gas puff imaging – divertor		X
Gas puff imaging – midplane		X
H $\alpha$ camera - 1D		X
High-k scattering		X
Infrared cameras		X
Interferometer - 1 mm		X
Langmuir probes – divertor		X
Langmuir probes – LLD		X
Langmuir probes – bias tile		X
Langmuir probes – RF ant.		X
Magnetics – B coils	X	
Magnetics – Diamagnetism		X
Magnetics – Flux loops	X	
Magnetics – Locked modes	X	
Magnetics – Rogowski coils	X	
Magnetics – Halo currents		X
Magnetics – RWM sensors	X	
Mirnov coils – high f.		X
Mirnov coils – poloidal array		X
Mirnov coils – toroidal array	X	
Mirnov coils – 3-axis proto.		X

*Note special diagnostic requirements in Sec. 4*

Diagnostic	Need	Want
MSE		X
NPA – E  B scanning		X
NPA – solid state		X
Neutron detectors	X	
Plasma TV	X	
Reflectometer – 65GHz		X
Reflectometer – correlation		X
Reflectometer – FM/CW		X
Reflectometer – fixed f		X
Reflectometer – SOL		X
RF edge probes		X
Spectrometer – divertor	X	
Spectrometer – SPRED	X	
Spectrometer – VIPS	X	
Spectrometer – LOWEUS	X	
Spectrometer – XEUS	X	
SWIFT – 2D flow		X
Thomson scattering	X	
Ultrasoft X-ray – pol. arrays	X	
Ultrasoft X-rays – bicolor		X
Ultrasoft X-rays – TG spectr.		X
Visible bremsstrahlung det.		X
X-ray crystal spectrom. - H		X
X-ray crystal spectrom. - V		X
X-ray tang. pinhole camera		X